





## Yuasa NP7-6 Industrial VRLA Battery

Sp	ec	ifi	ca	ti	OI	าร

Nominal voltage (V) 6 20-hr rate Capacity to 10.5V at 20°C (Ah) 7 10-hr rate Capacity to 10.8V at 20°C (Ah) 6.5

### **Dimensions**

Length (mm) 151 (±1)
Width (mm) 34 (±1)
Height over terminals (mm) 97.5 (±2)
Mass (kg) 1.32

### **Terminal Type**

FASTON - Quickfit / release (JST where stated) 4.75

## **Operating Temperature Range**

Storage (in fully charged condition)  $-20^{\circ}\text{C to } +60^{\circ}\text{C}$ Charge  $-15^{\circ}\text{C to } +50^{\circ}\text{C}$ Discharge  $-20^{\circ}\text{C to } +60^{\circ}\text{C}$ 

#### Storage

Capacity loss per month at 20°C (% approx.) 3

#### **Case Material**

Standard ABS (UL94:HB) FR version available UL94:V0

# **Charge Voltage**

Float charge voltage at 20°C (V)/Block 6.825 ( $\pm$ 1%) Float charge voltage at 20°C (V)/Cell 2.275 ( $\pm$ 1%) Float Chg voltage tmp correction factor from std -3

20°C (mV)

20°C (mV)

Cyclic (or Boost) charge Voltage at 20°C (V)/Block 7.26 (±3%)
Cyclic (or Boost) charge Voltage at 20°C (V)/Cell 2.42 (±3%)
Cyclic Chg voltage tmp correction factor from std -4

#### **Charge Current**

Float charge current limit (A)

Cyclic (or Boost) charge current limit (A)

No limit

1.75

## **Maximum Discharge Current**

1 second (A) 210 1 minute (A) 48

## **Impedance**

Measured at 1 kHz (m $\Omega$ ) 12

# **Design Life & Approvals**

EUROBAT Classification: Standard Commercial 3 to 5 Yuasa design life at 20°C (yrs) up to 5

## Art. no: SAANP7-6



### Layout



## **3rd Party Certifications**

ISO9001 - Quality Management Systems UNDERWRITERS LABORATORIES Inc.





# Safety

## Installation

Can be installed and operated in any orientation except permanently inverted.

#### Handles

Batteries must not be suspended by their handles (where fitted).

# Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

# Gas release

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

## Recycling

YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.









